

TECHNICAL SPECIFICATIONS

PATIO AWNINGS



MODEL	TORTOLA	BAHAMAS
DIMENSIONS		
Width:	1.71m - 5.50m	2.05m - 7.00m
Projections (arm size):	1.50m, 2.00m, 2.50m, 3.00m	1.50m, 2.00m, 2.50m, 3.00m, 3.50m, 3.75m
Fabric Width:	220mm less than o/a awning width	160mm less than o/a awning width
CASSETTE		
Material:	corrosion resistant, extruded aluminium	corrosion resistant, extruded aluminium
Face Fix Dimensions:	152mm high x 217mm deep	220mm high x 147mm deep
Top Fix Dimensions:	154mm high x 223mm deep	247mm high x 160mm deep
FOLDING ARMS		
Material:	corrosion resistant, extruded aluminium	corrosion resistant, extruded aluminium
Dimensions:	66mm high x 30mm wide	71mm high x 32.5mm wide
Wall Thickness:	2.5mm	2.5mm
Joints:	pressure die cast	pressure die cast
Tensioning System:	twin stainless steel cables	quadruple stainless steel cables
FRONT PROFILE		
Material:	corrosion resistant, extruded aluminium	corrosion resistant, extruded aluminium
Dimensions:	120mm high x 115mm deep	105mm high x 95mm deep
ROLLERTUBE		
Material:	galvanised steel	galvanised steel
Diameter:	78mm	78mm
Wall Thickness:	1.25mm	1.25mm
FIXING		
Face Fix:	standard	standard
Top Fix:	optional	optional
Points:	at each end of awning	multiple across width of awning
OPERATION		
Manual Via Gear Box & Handle:	standard	standard
Motorised Remote Control:	optional (choice of wirefree remote / wall switch)	optional (choice of wirefree remote / wall switch)
Automatic Via Sensors:	optional (choice of wind & light)	optional (choice of wind & light)
FABRICS		
Range:	lumera/elements	lumera/elements
HARDWARE FINISH		
Standard:	pure white or dark brown	pure white or dark brown
Custom:	any colour from the RAL series (200+)	any colour from the RAL series (200+)
DURABILITY		
Wind Rating:	beaufort 5 (class 2 under EN13561)	beaufort 5 (class 2 under EN13561)
OPTIONS		
Bespoke Brackets:	spreader plate, gutter bracket, stand off bracket	spreader plate, gutter bracket, stand off bracket
Drop Forged Arms:	not available	available for 3m proj + (beaufort 6 wind rating)

TECHNICAL SPECIFICATIONS AND INFORMATION CORRECT AT TIME OF GOING TO PRESS. WE RESERVE THE RIGHT TO MAKE TECHNICAL CHANGES AND IMPROVEMENTS WITHOUT NOTIFICATION.



**CARIBBEAN
BLINDS UK LTD**

UK MANUFACTURERS OF INNOVATIVE EXTERIOR BLINDS

Call: 0844 800 1947

Email: info@cbsolarshading.co.uk

Web: www.cbsolarshading.co.uk

